




T SERIES - EQUIPPED WITH SUPER HUB™

- External fluid path with machined from solid brass 90° full-flow NPT swivel inlet (Zinc plated steel swivel on HP models)
- Swivel Seals: NITRILE
- Sturdy dual pedestal reel features Coxreels' exclusive Super Hub™ dual axle support system
- Built for rugged mobile applications
- Multi-position lock ratchet mechanism secures hose at desired length



MODEL	EZ-Coil® Safety Line	I.D.	FT.	PSI	APRX. LBS.	W x H x L
TSH-N-350	EZ-TSH-350	3/8"	50	300	61	9 3/8 x 21 1/4 x 19 1/2"
TSH-N-375	EZ-TSH-375	3/8"	75	300	82	9 3/8 x 25 1/2 x 24"
TSH-N-3100	EZ-TSH-3100	3/8"	100	300	85	9 3/8 x 25 1/2 x 24"
TSH-N-450	EZ-TSH-450	1/2"	50	300	63	9 3/8 x 21 1/4 x 19 1/2"
TSH-N-475	EZ-TSH-475	1/2"	75	300	82	9 3/8 x 25 1/2 x 24"
TSH-N-4100	EZ-TSH-4100	1/2"	100	300	95	9 3/8 x 25 1/2 x 24"
TMP-N-350	EZ-TMP-350	3/8"	50	3,000	74	9 3/8 x 21 1/4 x 19 1/2"
TMP-N-375	EZ-TMP-375	3/8"	75	3,000	99	9 3/8 x 25 1/2 x 24"
TMP-N-3100	-	3/8"	100	3,000	106	9 3/8 x 25 1/2 x 24"
TMP-N-450	EZ-TMP-450	1/2"	50	2,500	77	9 3/8 x 21 1/4 x 19 1/2"
TMP-N-475	EZ-TMP-475	1/2"	75	2,500	100	9 3/8 x 25 1/2 x 24"
TMP-N-4100	-	1/2"	100	2,500	106	9 3/8 x 25 1/2 x 24"
TMP-N-550	EZ-TMP-550	3/4"	50	1,500	94	9 7/8 x 25 1/2 x 24"
TMP-N-575	-	3/4"	75	1,500	100	12 1/2 x 25 1/2 x 24"
TMP-N-650	-	1"	50	1,250	116	12 1/2 x 25 1/2 x 24"
THP-N-150	EZ-THP-150	1/4"	50	5,000	74	9 3/8 x 21 1/4 x 19 1/2"
THP-N-175	EZ-THP-175	1/4"	75	5,000	88	9 3/8 x 25 1/2 x 24"
THP-N-1100	EZ-THP-1100	1/4"	100	5,000	104	9 3/8 x 25 1/2 x 24"
THP-N-350	EZ-THP-350	3/8"	50	4,000	78	9 3/8 x 21 1/4 x 19 1/2"
THP-N-375	EZ-THP-375	3/8"	75	4,000	98	9 3/8 x 25 1/2 x 24"



P SERIES

- External fluid path with machined from solid brass 90° full-flow NPT swivel inlet (Zinc plated steel swivel on HP models)
- Swivel Seals: NITRILE
- Sturdy single pedestal spring driven reel with space saving design facilitates workplace organization

MODEL	EZ-Coil® Safety Line	I.D.	FT.	PSI	APRX. LBS.	W x H x L
P-LP-125	EZ-P-LP-125	1/4"	25	300	27	5 7/8 x 14 7/8 x 13 1/2"
P-LP-150	EZ-P-LP-150	1/4"	50	300	40	6 3/4 x 18 5/8 x 17 1/8"
P-LP-325	EZ-P-LP-325	3/8"	25	300	28	6 1/2 x 14 7/8 x 13 1/2"
P-LP-350	EZ-P-LP-350	3/8"	50	300	43	6 3/4 x 18 5/8 x 17 1/8"
P-LP-425	-	1/2"	25	300	44	7 x 18 5/8 x 17 1/8"
P-LP-450	EZ-P-LP-450	1/2"	50	300	48	7 x 18 5/8 x 17 1/8"
P-MP-325	-	3/8"	25	3,000	49	7 x 18 5/8 x 17 1/8"
P-MP-425	EZ-P-MP-425	1/2"	25	2,500	49	7 x 18 5/8 x 17 1/8"
P-HP-125	EZ-P-HP-125	1/4"	25	5,000	48	7 x 18 5/8 x 17 1/8"
P-HP-325	EZ-P-HP-325	3/8"	25	4,000	49	7 x 18 5/8 x 17 1/8"



SH, MP & HP SERIES - EQUIPPED WITH SUPER HUB™

- External fluid path with machined from solid brass 90° full-flow NPT swivel inlet (Zinc plated steel swivel on HP models)
- Swivel Seals: NITRILE
- Sturdy single pedestal spring driven reel features Coxreels' exclusive Super Hub™ dual axle support system



MODEL	EZ-Coil® Safety Line	I.D.	FT.	PSI	APRX. LBS.	W x H x L
SH-N-350	EZ-SH-350	3/8"	50	300	50	8 1/4 x 21 1/4 x 19 1/2"
SH-N-375	EZ-SH-375	3/8"	75	300	68	8 1/4 x 21 1/4 x 24"
SH-N-450	EZ-SH-450	1/2"	50	300	54	8 1/4 x 21 1/4 x 19 1/2"
SH-N-475	EZ-TSH-475	1/2"	75	300	68	8 3/4 x 25 1/2 x 24"
MP-N-350	EZ-MP-350	3/8"	50	3,000	65	8 1/4 x 21 1/4 x 19 1/2"
MP-N-450	EZ-MP-450	1/2"	50	2,500	67	8 3/4 x 25 1/2 x 19 1/2"
HP-N-150	EZ-HP-150	1/4"	50	5,000	64	8 3/4 x 25 1/2 x 19 1/2"
HP-N-350	EZ-HP-350	3/8"	50	4,000	65	9 1/4 x 25 1/2 x 19 1/2"



SG SERIES

- External fluid path with machined from solid brass 90° full-flow NPT swivel inlet (Zinc plated steel swivel on HP models)
- Swivel Seals: NITRILE
- Side mount design for vertical flat surface, cabinet or enclosed space mounts.

MODEL	EZ-Coil® Safety Line	I.D.	FT.	PSI	APRX. LBS.	W x H x L
SG13-L325	EZ-SG13-L325	3/8"	25	300	26	6 3/4 x 15 1/2 x 13 1/2"
SG17-L350	EZ-SG17-L350	3/8"	50	300	40	6 3/4 x 19 1/2 x 17"
SG17-L430	EZ-SG17-L430	1/2"	30	300	42	6 3/4 x 19 1/2 x 17"
SG19-L450	EZ-SG19-L450	1/2"	50	300	52	8 1/2 x 22 x 19 1/2"
SG19-M350	EZ-SG19-M350	3/8"	50	3,000	63	8 1/2 x 22 x 19 1/2"
SG19-M450	EZ-SG19-M450	1/2"	50	2,500	65	9 3/8 x 22 x 19 1/2"
SG19-H150	EZ-SG19-H150	1/4"	50	5,000	62	9 x 22 x 19 1/2"
SG19-H350	EZ-SG19-H350	3/8"	50	4,000	63	9 1/2 x 22 x 19 1/2"



E SERIES

- External fluid path with machined from solid brass 90° full-flow NPT swivel inlet (Zinc plated steel swivel on HP models)
- Swivel Seals: NITRILE
- Solid one piece, heavy gauge 1/4" steel base & support post for maximum stability
- Designed for expandable metal cabinets & multiple reel bank system

MODEL	EZ-Coil® Safety Line	I.D.	FT.	PSI	APRX. LBS.	W x H x L
E-LP-330	EZ-E-LP-330	3/8"	30	300	33	6 1/8 x 18 1/4 x 17 1/4"
E-LP-350	EZ-E-LP-350	3/8"	50	300	46	8 3/4 x 21 x 19 5/8"
E-LP-430	EZ-E-LP-430	1/2"	30	300	41	6 1/8 x 18 1/4 x 17 1/4"
E-LP-450	EZ-E-LP-450	1/2"	50	300	50	8 3/4 x 21 x 19 5/8"
E-MP-330	EZ-E-MP-330	3/8"	30	3,000	47	6 1/8 x 18 1/4 x 17 1/4"
E-MP-350	EZ-E-MP-350	3/8"	50	3,000	61	8 3/4 x 21 x 19 5/8"
E-MP-430	EZ-E-MP-430	1/2"	30	2,500	47	6 1/8 x 18 1/4 x 17 1/4"
E-MP-450	EZ-E-MP-450	1/2"	50	2,500	63	8 3/4 x 21 x 19 5/8"
E-HP-130	EZ-E-HP-130	1/4"	30	5,000	46	7 x 18 1/4 x 17 1/4"
E-HP-150	EZ-E-HP-150	1/4"	50	5,000	60	9 1/4 x 21 x 19 5/8"
E-HP-330	EZ-E-HP-330	3/8"	30	4,000	47	7 x 18 1/4 x 17 1/4"
E-HP-350	EZ-E-HP-350	3/8"	50	4,000	61	9 1/4 x 21 x 19 5/8"



EXPANDABLE METAL CABINETS

- Unlimited expandability
- All steel access panel
- Cabinet constructed of 14 gauge steel with 4-roller non-sag hose guide system for reduced hose wear
- Mounting bracket is 3/16" bent steel, fits 3" to 8 1/2" flange on "I" or "H" beam
- Easy access for connection of air, water, oil & grease

PART NO.	DESCRIPTION	APRX. LBS.	W x H x L
1796-2	METAL CABINET: includes cabinet, access panel & mounting bracket	45	24 1/2 x 11 1/8 x 22 1/4"
1798-1	END PANELS: includes a set of two, all steel construction. Finished & caps the ends of each bank	8	-

This selection only represents a sample of products applicable in this industry. Please visit us online or consult the factory for more product options.